



### **DELDOT GENERAL NOTES:**

- ALL ENTRANCES SHALL CONFORM TO THE DELAWARE DEPARTMENT OF TRANSPORTATION'S (DELDOT'S) CURRENT DEVELOPMENT COORDINATION MANUAL AND SHALL BE SUBJECT TO ITS APPROVAL.
- AS OF THE ISSUANCE OF THE NOTICE TO PROCEED (NTP) ALL MATERIALS AND WORKMANSHIP WITHIN THE STATE OF DELAWARE RIGHT-OF-WAY SHALL BE IN ACCORDANCE WITH CURRENT STATE OF DELAWARE DEPARTMENT OF TRANSPORTATION STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION, SUPPLEMENTAL SPECIFICATIONS, STANDARD CONSTRUCTION DETAILS, SPECIAL PROVISIONS, PAS MANUAL AND DESIGN
  - ALL DISTURBED AREAS WITHIN THE STATE RIGHT-OF-WAY, BUT NOT IN THE PAVEMENT, SHALL BE TOP-SOILED (6" MINIMUM), FERTILIZED, SEEDED AND MULCHED. IF SOD IS USED NEXT TO SIDEWALK OR SHARED-USE PATH, CONTRACTOR SHALL GRADE TOPSOIL ADJACENT TO THE SIDEWALK OR SHARED-USE PATH PRIOR TO PLACEMENT OF SOD TO ENSURE THAT SOD IS PLACED FLUSH OR JUST BELOW EDGE OF SIDEWALK OR SHARED-USE
  - PATH TO AVOID WATER PONDING ON THE SIDEWALK OR SHARED-USE PATH. A 72-HOUR (MINIMUM) NOTICE SHALL BE GIVEN TO THE DELDOT DISTRICT PERMIT SUPERVISOR PRIOR TO STARTING ENTRANCE CONSTRUCTION.
  - MISS UTILITY OF DELAWARE SHALL BE NOTIFIED THREE (3) CONSECUTIVE WORKING DAYS PRIOR TO EXCAVATION, AT 1-800-282-8555.
  - THE DEVELOPER SHALL BE REQUIRED TO FURNISH AND PLACE RIGHT-OF-WAY MONUMENTS IN ACCORDANCE WITH DELDOT'S DEVELOPMENT
  - AT THE DISCRETION OF THE PUBLIC WORKS INSPECTOR, ANY DAMAGED, NON-COMPLIANT OR MISSING CURB OR SIDEWALK FOUND ON SITE WILL NEED TO BE REPAIRED OR REPLACED TO MEET CURRENT DELDOT STANDARDS.
  - AS OF THE ISSUANCE OF THE NOTICE TO PROCEED (NTP), ALL SIGNING, STRIPING, AND MAINTENANCE OF TRAFFIC IS THE CONTRACTOR'S RESPONSIBILITY AND SHALL FOLLOW THE GUIDELINES SHOWN IN THE DELAWARE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (DELAWARE MUTCD) FOR STREETS AND HIGHWAYS. THE DEVELOPER OR PROPERTY OWNERS SHALL BE RESPONSIBLE FOR MAINTENANCE OF ALL SIGNS
  - PLAN LOCATION AND DIMENSIONS SHALL BE STRICTLY ADHERED TO UNLESS OTHERWISE DIRECTED BY THE DELDOT INSPECTOR.
  - 10. A COPY OF THE-UP-TO DATE APPROVED CONSTRUCTION DOCUMENTS AND DELDOT APPROVAL LETTERS SHALL BE MAINTAINED ON THE PROJECT SITE AT ALL TIMES AND BE AVAILABLE FOR INSPECTION BY DELDOT PERSONNEL.
  - EXISTING UTILITIES ARE SHOWN IN ACCORDANCE WITH THE BEST AVAILABLE INFORMATION. COMPLETENESS OR CORRECTNESS THEREOF IS NOT GUARANTEED. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO CONTACT THE UTILITY COMPANIES INVOLVED IN ORDER TO SECURE THE MOST ACCURATE INFORMATION AVAILABLE AS TO LITH ITY LOCATION AND ELEVATION, NO CONSTRUCTION AROUND OR ADJACENT TO LITH ITIES SHALL BEGIN WITHOUT NOTIFYING THEIR OWNERS AT LEAST 48-HOURS IN ADVANCE. THE CONTRACTOR SHALL TAKE THE NECESSARY PRECAUTIONS TO PROTECT THE EXISTING UTILITIES AND MAINTAIN UNINTERRUPTED SERVICE AND ANY DAMAGE DONE TO THEM DUE TO HIS/HER NEGLIGENCE SHALL BE IMMEDIATELY AND COMPLETELY REPAIRED AT THE CONTRACTOR'S EXPENSE. TO LOCATE EXISTING UTILITIES IN THE FIELD PRIOR TO CONSTRUCTION, THE CONTRACTOR SHALL CONTACT MISS UTILITY OF DELAWARE (SEE NOTE #5).
  - SHOULD UTILITY RELOCATION BE REQUIRED. THE DEVELOPER MUST SUBMIT A UTILITY RELOCATION PLAN FOR DELDOT REVIEW. ALONG WITH CORRESPONDENCE FROM THE UTILITY COMPANIES STATING PRELIMINARY APPROVAL TO THE RELOCATION AND DESIGN OF THE UTILITIES PRIOR TO THE DELDOT PRE-CONSTRUCTION MEETING. NO PHYSICAL CONSTRUCTION CAN OCCUR UNTIL THE UTILITY PLANS ARE APPROVED. THE INDIVIDUAL UTILITY COMPANIES ISSUE FINAL APPROVAL, AND A DELDOT UTILITY PERMIT IS ISSUED TO THE UTILITY COMPANY.
  - . UPON COMPLETION OF THE CONSTRUCTION OF THE SIDEWALK OR SHARED-USE PATH ACROSS THIS PROJECT'S FRONTAGE AND PHYSICAL CONNECTION TO ADJACENT EXISTING FACILITIES. THE DEVELOPER THE PROPERTY OWNERS OR BOTH ASSOCIATED WITH THIS PROJECT. SHALL BE RESPONSIBLE TO REMOVE ANY EXISTING ROAD TIE-IN CONNECTIONS LOCATED ALONG ADJACENT PROPERTIES, AND RESTORE THE AREA TO GRASS. THESE DISTURBED AREAS SHALL BE TOP-SOILED (6" MINIMUM), FERTILIZED, SEEDED AND MULCHED. SUCH ACTIONS SHALL BE COMPLETED AT DELDOT'S DISCRETION, AND IN CONFORMANCE WITH THE DEVELOPMENT COORDINATION MANUAL
  - 4. DELDOT WILL NOT PROVIDE THE RESPECTIVE LOCAL LAND USE AGENCY WITH A 'NO OBJECTION TO THE ISSUANCE OF THE CERTIFICATE OF OCCUPANCY NOTICE' UNTIL THE ENTRANCE(S) ARE COMPLETED TO THE SATISFACTION OF THE DEPARTMENT
  - 15. DESIGN, FABRICATION AND INSTALLATION OF ALL PERMANENT SIGNING SHALL BE AS OUTLINED IN THE LATEST VERSION OF THE DELAWARE MUTCD.
  - 16. DESIGN AND INSTALLATION OF ALL PAVEMENT MARKINGS AND STRIPING SHALL BE AS OUTLINED IN THE LATEST VERSION OF THE DELAWARE MUTCD. FOR FINAL PERMANENT PAVEMENT MARKINGS:
  - 16.b. THERMO PLASTIC (EXTRUDED OR PREFORMED MATERIAL) WILL BE REQUIRED ON ASPHALT SURFACES, FOR SHORT LINE STRIPING, I.E.
  - 16.c. PERMANENT PAVEMENT MARKING TAPE (PER DELDOT'S APPROVED MATERIALS LIST) WILL BE REQUIRED ON CONCRETE SURFACES, FOR SHORT LINE STRIPING, I.E. SYMBOLS/LEGENDS.
  - 7. REMOVAL OF PAVEMENT MARKING PAINT OR TAPE SHALL COMPLY WITH SECTION 5.11.2 OF THE DEVELOPMENT COORDINATION MANUAL. 18. BREAKAWAY POSTS SHALL BE USED WHEN INSTALLING ALL SIGNS. REFERENCE DELDOT'S STANDARD CONSTRUCTION DETAILS, SECTION VIII -

  - 19.a. THE ENDS OF ALL CURBS SHALL BE TRANSITIONED TO BE FLUSH WITH THE PAVEMENT AT A RATIO OF TWELVE TO ONE (12:1).
  - 19.b. ALL APPROACH AND EXIT ENDS OF MEDIAN ISLAND AND CURB SHALL ALSO BE TRANSITIONED FLUSH WITH THE PAVEMENT AT A RATIO OF TWELVE
- SECTION 5.5.5 OF THE DEVELOPMENT COORDINATION MANUAL. ANY FIXED OBJECT THAT DOES NOT MEET THIS REQUIREMENT SHALL BE RELOCATED 21. IT IS THE CONTRACTOR'S RESPONSIBILITY TO ENSURE THAT ALL PAVING WITHIN THE STATE OF DELAWARE RIGHT-OF-WAY IS INSTALLED TO THE
- ELEVATIONS SHOWN AND NO PONDING OF WATER EXISTS AFTER PAVING IS COMPLETE. 22. ALL STORM DRAIN PIPING DESIGNATED AS REINFORCED CONCRETE PIPE IS TO BE REINFORCED CONCRETE PIPE, MEETING AASHTO M-170
- 3. ALL PROPOSED CLOSED STORMDRAIN SYSTEMS SHALL BE VIDEO INSPECTED, REPAIRED AS NECESSARY AND APPROVED PRIOR TO THE INSTALLATION OF FINAL PAVING. IF REPAIRS ARE NEEDED, THE REPAIRED PIPE SECTIONS WILL NEED TO BE VIDEO INSPECTED AGAIN BEFORE THE
- THE DEVELOPER AND EXISTING/FUTURE OWNER OF NON-STATE-MAINTAINED ROADWAYS SHALL ENSURE THAT THE TRAFFIC CONTROL DEVICES ON SAID ROADWAYS OPEN TO PUBLIC TRAVEL ARE IN COMPLIANCE WITH THE LATEST VERSION OF THE DELAWARE MUTCD.
- $25.\,\,$  ALL SUBGRADE SHALL BE COMPACTED TO 95% OF THE MAXIMUM STANDARD T-99 DRY DENSITY.
- 26. THE CONTRACTOR SHALL NOTIFY DART FIRST STATE AT <u>DOT\_DETOURS@DELAWARE.GOV</u> AT LEAST 14 DAYS PRIOR TO THE START OF ANY DETOURS OR CONSTRUCTION, AND <u>DOT\_DTC\_PROJECTDEVELEOPMENT@DELAWARE.GOV</u> AT SUCH TIME THE FACILITY IS COMPLETED AND OPERABLE FOR TRANSIT OPERATIONS. FOR EMERGENCY DETOUR INFORMATION <u>ONLY</u> PLEASE CONTACT DTC'S CHIEF SCHEDULER AT 302-576-6019.
- 27. FOR INFORMATION ON OBTAINING A UTILITY PERMIT IN NEW CASTLE COUNTY CONTACT M&O-CANAL DISTRICT-PUBLIC WORKS AT (302) 326-4679.
- 28. FOR INFORMATION ON GETTING APPROVAL FOR PROPOSED OUTDOOR ADVERTISING IN NEW CASTLE COUNTY CONTACT M&O-CANAL DISTRICT-OUTDOOR ADVERTISING/ROADSIDE CONTROL AT (302) 326-4688.

#### **DELDOT NOTES: DELDOT ISSUED 03/21/19**

- ALL ENTRANCES SHALL CONFORM TO THE DELAWARE DEPARTMENT OF TRANSPORTATION'S (DELDOT'S) DEVELOPMENT COORDINATION MANUAL (DCM) AND SHALL BE SUBJECT TO ITS APPROVAL
- UPON COMPLETION OF THE CONSTRUCTION OF THE SIDEWALK OR SHARED-USE PATH ACROSS THIS PROJECT'S FRONTAGE AND PHYSICAL CONNECTION TO ADJACENT EXISTING FACILITIES, THE DEVELOPER, THE PROPERTY OWNERS OR BOTH ASSOCIATED WITH THIS PROJECT, SHALL BE RESPONSIBLE TO REMOVE ANY EXISTING ROAD TIE-IN CONNECTIONS LOCATED ALONG ADJACENT PROPERTIES. AND RESTORE THE AREA TO GRASS SUCH ACTIONS SHALL BE COMPLETED AT DELDOT'S DISCRETION, AND IN CONFORMANCE WITH DELDOT'S DEVELOPMENT COORDINATION MANUAL
- TO MINIMIZE RUTTING AND EROSION OF THE ROADSIDE DUE TO ON-STREET PARKING, DRIVEWAY AND BUILDING LAYOUTS MUST BE CONFIGURED TO ALLOW FOR VEHICLES TO BE STORED IN THE DRIVEWAY BEYOND THE RIGHT-OF-WAY, WITHOUT INTERFERING WITH SIDEWALK ACCESS AND
- AT THE DISCRETION OF THE PUBLIC WORKS INSPECTOR, ANY DAMAGED OR MISSING CURB OR SIDEWALK FOUND ON SITE WILL NEED TO BE REPAIRED OR REPLACED TO MEET CURRENT DELDOT STANDARDS

TRAFFIC GENERATION DIAGRAM

A.D.T. (A.M. PK) [P.M. PK]

**OTTS CHAPEL ROAD** 

(N-397)

TRAFFIC GENERATION DIAGRAM

A.D.T. (A.M. PK) [P.M. PK]

**ELKTON ROAD** 

,794 (128) [110] 🖚

CONSTRUCTION WILL NOT BE PERMITTED UNTIL CONSTRUCTION PLANS HAVE BEEN APPROVED. SURETY HAS BEEN RECEIVED AND THE TRAFFIC SIGNAL AGREEMENT IS COMPLETE. AT DELDOT'S DISCRETION, A TEMPORARY CONSTRUCTION ENTRANCE PERMIT MAY BE ISSUED FOR CLEARING. GRUBBING, TEMPORARY ENTRANCE CONSTRUCTION, BULK GRADING AND PERIMETER EROSION AND SEDIMENT CONTROLS UP TO THIRTY (30) DAYS PRIOR TO PLAN APPROVAL. NO BUILDING CONSTRUCTION WILL BE PERMITTED UNDER A TEMPORARY ENTRANCE CONSTRUCTION PERMIT. IF PLAN APPROVAL IS NOT RECEIVED WITHIN THIRTY (30) CALENDAR DAYS, ALL CONSTRUCTION ACTIVITIES SHALL BE STOPPED. DELDOT WILL NOT RECOMMEND A CERTIFICATE OF OCCUPANCY APPROVAL FOR A COMMERCIAL ENTRANCE TO NCC UNTIL THE ENTRANCE(S) ARE COMPLETED TO T

430 (31) [26]

**ROAD TRAFFIC DATA:** 

**ROAD TRAFFIC DATA:** 

NCR-11 (ELKTON ROAD) - SPEED LIMIT = 50 MPH

SITE TRIPS GENERATED:

ITE: 945 - CONVENIENCE STORE / GAS STATION

(255 IN / 256 OUT)

(220 IN / 221 OUT)

1,794 ADT (128 AM) [110 PM

430 ADT (31 AM) [26 PM]

1,363 ADT (96 AM) [84 PM]

A.M. PEAK HR. TRIPS = 511 (50% IN / 50% OUT)

P.M. PEAK HR. TRIPS = 441 (50% IN / 50% OUT)

36% EXITING TO S.B. OTTS CHAPEL RD:

50% ENTERING FROM E.B. ELKTON RD

12% ENTERING FROM W.B. OTTS CHAPEL RD

38% ENTERING FROM F B OTTS CHAPFL RD:

DESIGN VEHICLE: WB-62

TRAFFIC PATTERN GROUP:

[VFP (16-24)] (5,585 S.F.)

DIRECTIONAL DISTRIBUTION

DESIGN VEHICLE: WB-62 K FACTOR: 10.20%

D FACTOR: 57.40%

K FACTOR: 11.90%

D FACTOR: 61.40%

NCR-397 (OTTS CHAPEL ROAD) - SPEED LIMIT = 40 MPH

AADT = 18,107 TRIPS (FROM 2021 DelDOT TRAFFIC COUNTS)

0 YEAR PROJECTED AADT: 1.16 x 18,107 = 21,005 TRIPS

# G R O U

DELDOT ISSUED 03/14/22

ARCHITECTURE ENGINEERING

> 309 S. Governors Ave. Dover, DE 19904 Ph 302 734 7950

Dover, DE

Fax 302.734.7965 Salisbury, MD

312 West Main St. Suite 300 Salisbury, MD 21801 Ph. 410.546.9100 Fax 410.546.5824

Wilmington, NC 3333 Jaeckle Rd, Suite 120 Wilmington, North Carolina 28403

Fax 910.341.7506 www.beckermorgan.com

Ph. 910.341.7600

# CONVENIENCE **STORE WITH** GAS

REZONING, MINOR SUBDIVISION, **ANNEXATION, & SPECIAL USE** PR#18-07-01

1105 ELKTON ROAD **NEWARK, DE 19711** PENCADER HUNDRED **NEW CASTLE COUNTY** 

## SHEET TITLE **COVER SHEET AND DELDOT NOTES**

ISSUE BLOCK 3 | 11/9/21 | AGENCY SUBMISSION AGENCY SUBMISSION 2 7/7/21 AGENCY SUBMISSION 4/20/21 MARK DATE DESCRIPTION PROJECT NO.: DATE:

AADT = 29,655 TRIPS (FROM 2021 DelDOT TRAFFIC COUNTS) DESIGN VEHICLE: WB-62 SOURCE: ITE TRIP GENERATION MANUAL (11TH EDITION) TOTAL SITE ADT: 1,283.38 x (5,585/1,000) = 7,174 TRIPS (50% IN / 50% OUT) = 3,587 IN / 3,587 OUT **SCALE:** 

2017244.0° 06/29/20 DRAWN BY: J.D.K. PROJ. MGR.: C.D.D

F:\AutoCAD\Projects\2017\2017244.01\DWG\201724401-SITE-C3D18.dwg, Oct 19, 2022 - 9:14an









